

Revision Date: 25-Mar-2024

Supersedes: 12-Nov-2019

Mica Interference Green

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / March 26, 2012 / Rules and Regulation

PRODUCT & COMPANY IDENTIFICATION

Product Name: Mica Interference Green

Synonyms: No data available

INCI Name: Titanium Dioxide, Mica, Silica 13463-67-7, 12001-26-2, 7631-86-9 CAS Number:

Formula: No data available

Product Form: Solid

Cosmetic use **Product Use:**

Distributor: MakingCosmetics Inc. 10800 231st Way NE Address: Redmond, WA 98053 (USA)

Phone / Fax: 425-292-9502 / 425-292-9601 Web: www.makingcosmetics.com

Emergency Telephone Number: 1-800-424-9300 (Chemtrec)

HAZARDS IDENTIFICATION

GHS Classification: Not a hazardous substance or mixture. **GHS Labeling:** Not a hazardous substance or mixture.

GHS Hazard Pictograms: None. **GHS Hazard Statements:** None. **GHS Precautionary Statements:** None.

Potential Health Hazards: Eves: May be an irritant.

> Inhalation: May be an irritant. Skin: Not expected to be an irritant.

Ingestion: May cause nausea, vomiting, or diarrhea.

NFPA Ratings (704):

Health N/A N/A Flammability N/A N/A Reactivity N/A N/A

Specific Hazard N/A

COMPOSITION/INFORMATION ON INGREDIENTS

Molecular Weight Component CAS No. Weight % Titanium Dioxide 13463-67-7 57 - 67% Not Available 12001-26-2 19 - 33% Not Available Mica Silica 7631-86-9 10 - 14% Not Available

FIRST AID MEASURES

Rinse out with plenty of water. Remove contact lenses. Seek medical attention if necessary. Eyes:

Inhalation: Move to fresh air. Seek medical attention if necessary.

Skin: Take off immediately all contaminated clothing. Rinse skin with water/shower. Seek medical attention if

necessary.

Make victim drink water (two glasses at most). Do Not Induce Vomiting! Never give anything by mouth to an Ingestion:

unconscious person. Seek medical attention if feeling unwell.

FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

chemical:

Special protective equipment & precautions for firefighters: Specific hazards arising from the Use extinguishing measures that are appropriate to local circumstances and the surrounding environment for adjacent fire. No unsuitable extinguish media listed.

Use air supplied breathing apparatus and full protective clothing, including eye protection and boots. Suppress gases/vapors/mists with a water spray iet.

Not combustible. Ambient fire may liberate hazardous vapors.



ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment & emergency procedures:

Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Do not try to clean up the leak without proper protective equipment. See section 8 for recommendations on the use of personal protective equipment.

Avoid liquid release into sewers/public water/environment. Notify environmental

authorities in case of leak.

Methods and material for containment and cleaning up:

Environmental precautions:

Observe possible material restrictions. Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dust. Do not try to clean up the leak without the proper protective equipment. Dispose of all waste and cleanup materials in accordance with regulations.

HANDLING & STORAGE

Precautions for safe handling:

Conditions for safe storage, incl. any incompatibilities:

Observe label precautions. Handle in accordance with good industrial hygiene and safety practices. See section 8 for recommendations on the use of personal protective equipment.

Store tightly closed and dry, away from incompatible materials (see section 10 for incompatibilities).

EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	Exposure Limits	<u>Basis</u>	Entity
General threshold limit value	15 mg/m3 (total dust)	TWA	OSHA Z-3
for dust			
	5 mg/m3 (respirable fraction)	TWA	OSHA Z-3
	50 million particles per cubic	TWA	OSHA Z-3
	Foot (total dust)		
	15 million particles per cubic	TWA	OSHA Z-3
	Foot (respirable fraction)		
Titanium(IV) oxide (Titanium	15 mg/m3 (total dust)	TWA	OSHA Z-1
Dioxide)	is ing. ine (count dues)		
	10 mg/m3 (total dust)	TWA	OSHA PO
	10 mg/m3 (respirable fraction)	TWA	ACGIH
Mica (muscovite)	3 mg/m3 (respirable fraction)	TWA	OSHA PO
()	3 mg/m3 (respirable)	TWA	NIOSH REL
	20 million particles per cubic	TWA	OSHA Z-3
	Foot (dust)	. , , , ,	031.171.2.3
	3 mg/m3 (respirable fraction)	TWA	ACGIH
Silicon dioxide (Silica)	80 mg/m3 / %SiO2 (dust)	TWA	OSHA Z-3
Sitieon dioxide (Sitied)	6 mg/m3 (dust)	TWA	NIOSH REL
	20 million particles per cubic	TWA	OSHA Z-3
	·	IVVA	OSI IA Z-3
	foot (dust)		

TWA: Time Weighted Average over 8 hours of work. TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes. IDLH: Immediately Dangerous to Life or Health WEEL: Workplace Environmental Exposure Levels

CEIL: Ceiling

Personal Protection:

Eyes: Wear safety glasses.

Inhalation: Air purifying masks are required when dust is generated.

Body: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when

handling chemical products.

Other: Technical measures and appropriate working operations should be given priority over the use of personal protective

equipment. Use good personal hygiene practices. Change contaminated clothing. Wash hands after working with substance. Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use

and handling.

PHYSICAL AND CHEMICAL PROPERTIES



Powder Appearance: Odor: **Odorless** Odor Threshold: Not applicable Color: Light yellow No data available Molecular Weight:

pH at 68°F (20 °C): 8.0 - 11.0 at 100 g/l (slurry) **Boiling Point:** No data available

Bulk Density: 320 - 380 kg/m3

Density at 68°F (20°C):

Partition Coefficient: noctanol/water:

Oxidizing Properties:

3.0 - 3.3 g/cm3

log Pow: < 0.5

(20°C): **Auto-Ignition Temperature:**

Particle Size:

Specific Gravity:

Vapor Pressure:

Evaporation Rate:

Flammability (solid, gas):

Water Solubility at 68°F

Upper/lower Explosive Limit:

Vapor Density:

Flash Point:

No data available 10.0 - 60.0 um (particle size)

No data available

Practically insoluble

Not flammable

18.0 - 25.0 µm (mean particle

size)

Explosive Properties: Not classified as explosive

10 STABILITY AND REACTIVITY

Reactivity: The product is chemically stable under standard ambient conditions (room temperature). Chemical Stability: The product is chemically stable under standard ambient conditions (room temperature).

Hazardous Polymerization: No data available. No data available. Conditions to Avoid: Incompatible Materials: No data available.

Hazardous Decomposition Products: In the event of fire: see section 5.

None

Possible Hazardous Reactions: No data available.

TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

Titanium Dioxide: (Rat) LD50: > 10,000 mg/kg.

Silica: (Rat) LD50: > 5,000 mg/kg (OECD Test Guideline 401(ECHA)).

Skin

Titanium Dioxide: (Rabbit) Result: No skin irritation (IUCLID). Silica: (Rabbit) LD50: > 5,000 mg/kg (IUCLID).

Eyes

Titanium Dioxide: (Rabbit) Result: No eye irritation (IUCLID).

(Rabbit): no irritant effect (OECD Test Guideline 405 (IUCLID)). Silica:

Respiratory

Silica: (Rat) LC50: Male animals: between 4.6 and 14.9 mg/l air; female animals: > 14.9 mg/l air.

Rat LC50: > 0.14 mg/l; 4 hours; dust/mist (highest concentration to be prepared) (OECD Test

Guideline 403 (ECHA)).

Ingestion: (Rat) LD50: not determinable; all animals still alive after 15,000 mg/kg.

Likely Route of Exposure: Inhalation, eye contact, skin contact, ingestion.

Carcinogenicity

IARC: Group 2B: Possibly carcinogenic to humans (titanium(IV) oxide) 13463-67-7).

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of

regulated carcinogens.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

Did not show mutagenic or teratogenic effects in animal experiments. Teratogenicity:

Genotoxic Effects: The product did not show any genotoxic effects in the micronucleus test carried out in rats in

concentrations of up to 2000 mg/kg (limit test).

Genotoxicity in Vivo/Vitro: (Rat) In Vivo: negative (ECHA).

(Salmonella typhimurium) In Vitro Ames test: Negative (IUCLID).

(Chinese hamster ovary cells) Chromosome aberration test in vitro: Negative; Metabolic activation: with and without metabolic activation (OECD Test Guideline 473 (ECHA)). Result: negative (IUCLID) CMR effects. Animal testing did not show any mutagenic effects.

Mutagenicity:

Specific Target Organ Toxicity

Silica:

(Rat) Repeated exposure, Oral: 13 Weeks; daily; NOAEL: 4,000 mg/kg (OECD Test Guideline 408

(ECHA)).



(Rat) Repeated exposure, Inhalation: 13 Weeks; daily (OECD Test Guideline 413(ECHA))

Single Exposure: The substance or mixture is not classified as specific target organ toxicant.

No toxicity to reproduction.

Chronic Toxicity: (Rat): 5 % of the product added to the feed for a period of 2.5 years did not show any

toxicological changes or carcinogenic effects in animals.

Subchronic Toxicity: (Rat): no findings up to 20,000 ppm.

Sensitization: Did not cause sensitization on laboratory animals.

Titanium Dioxide: (Mouse) Local lymph node assay (LLNA): Negative (OECD Test Guideline 429 (ECHA)).

Silica: (Guinea pig): No sensitizing potential (IUCLID).

Additional Toxicity Information: The results of animal experiments using pigments of this type indicate no toxicologically

relevant properties. Since the substance is poorly absorbed, no hazardous properties are to be

anticipated. Inhalation of the dusts should be avoided as even inert dusts may impair

respiratory organ functions.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No ecological problems are to be expected when the product is handled and used with due care

and attention.

Aquatic Vertebrate

Reproductive Toxicity:

Titanium Dioxide: (Golden orfe) LC0 Leuciscus idus: > 1,000 mg/l.

Silica: (Danio rerio) Static test LC50: 10,000 mg/l; 96 hours (OECD Test Guideline 203 (ECHA)).

(Fish) Chronic Toxicity: NOEC 86.03 mg/l; 30 days.

Aquatic Invertebrate

Silica: (Daphnia magna) Static test EC50: > 1,000 mg/l; 24 hours (OECD Test Guideline 202 (ECHA)).

(Daphnia magna) Chronic Toxicity: NOEC: 34.2 mg/l; 30 days (ECHA).

Terrestrial

Titanium Dioxide: (Pseudomonas fluorescens) ECO: > 5,000 mg/l.

Silica: (Pseudokirchneriella subcapitata) IC50: 440 mg/l; 72 hours (IUCLID).

(Pseudokirchneriella subcapitata) NOEC: 60 mg/l; 72 hours (IUCLID).

Persistence and Degradability

Titanium Dioxide: Not readily biodegradable.

Silica: The methods for determining biodegradability are not applicable to inorganic substances.

Bioaccumulative Potential: Bioaccumulation is not expected.

Mobility in Soil:

No data available.

PBT and vPvB Assessment: No data available. Other Adverse Effects: No data available.

13 DISPOSAL CONSIDERATIONS

Waste Residues: Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the

product itself. Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary, before disposing of waste product

container.

Product Containers: Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the

product itself. Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary, before disposing of waste product

container.

The information in section 13 is for the product as shipped. Use and/or alterations to the product may change the characteristics of the material and alter the waste classification and proper disposal methods

14 TRANSPORT INFORMATION

DOT (Dept. of Transportation, USA):

TDG (Transportation of Dangerous Goods, Canada):

IMDG (International Maritime Dangerous Goods):

IATA (International Air Transport Association):

ICAO (International Civil Aviation Organization):

Not regulated as dangerous goods.



15 REGULATORY INFORMATION

TSCA Inventory Status: This product is regulated under the Food, Drug, and Cosmetic Act and is exempt from TSCA.

CERCLA Reportable Quantity: This material does not contain any components with a CERCLA RQ.

SARA 304: This material does not contain any components with a section 304 EHS RQ.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section

302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the

threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by

the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air

Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for

Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI

Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act: This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act,

Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean Water Act,

Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section

307.

MA Right to Know: Titanium (IV) oxide 13463-67-7, Mica (muscovite) 12001-26-2, Silicon dioxide 7631-86-9
PA Right to Know: Titanium (IV) oxide 13463-67-7, Mica (muscovite) 12001-26-2, Silicon dioxide 7631-86-9

NJ Right to Know: Titanium (IV) oxide 13463-67-7, Mica (muscovite) 12001-26-2 Canada (DSL): All components of this product are on the Canadian DSL

California Prop. 65: WARNING: This product can expose you to chemicals including titanium (IV) oxide (13463-67-7),

which is known to the State of California to cause cancer. For more information, go to

www.P65Warnings.ca.gov

16 OTHER INFORMATION

Revision Date: 25-Mar-2024

Compliance: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication

Standard 29 CFR 1910.1200

Disclaimer: This information relates only to the specific material designated and may not be valid for such material used in

combination with any other materials or in any other process. Such information is to be the best of the

company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness & completeness of such information for his

own particular use.